

BRAVO STILL

SILENT & ENERGY SAVING

Features



- Wall and ceiling mounting
- Easy maintenance
- Continuous operation
- Backdraft damper
- Ball bearing motor
- Available in chrome (Bravo Still Chrome) and platinum (Bravo Still Platinum) decorations
- 5 year warranty



Air flow:
up to 235 m³/h
65 l/s



Power:
from 5.6 W
SFP:
from 0.29 W/l/s



Noise level:
from 26 dBA



Chrome



Platinum

Options




Model	Bravo Still 100/125/150					
Option	S	T	ST	H	SH	IR
Pull-cord switch	•		•		•	
Timer		•	•	•	•	•
Humidity sensor				•	•	
Motion sensor						•

- Turn-off delay adjustable from 2 to 30 min.
- Humidity setpoint adjustable from 60 % up to 90 %.
- Detection range from 1 up to 4 m.
- Detection angle up to 100°.


Technical data

Model	Bravo Still 100	Bravo Still 125	Bravo Still 150
Voltage [V/Hz]	220-240/50	220-240/50	220-240/50
Power [W]	5.6	9.3	20
Current [A]	0.04	0.006	0.13
Air flow [m³/h (l/s)]	70 (19)	115 (32)	235 (65)
SFP [W/l/s]	0.29	0.29	0.31
Noise level [dBA]	26	31	35




CE GS IP34

Overall dimensions and mounting



Dimensions [mm]	a	b	c	Ø d	e
Bravo Still 100	150	122	102	100	17
Bravo Still 125	176	144	104	125	17
Bravo Still 150	205	174	124	150	19



Designation key

Bravo	Still	Chrome	100	S
Model	Low-noise application	Color	Spigot diameter	Option

Accessories

Duct system



BlauPlast

Flexible air ducts



BlauFlex

Grilles and hoods



Decor, GM

Speed controllers



CDT E1.8

MCD 60/0.3

Clamps



K, KZ